

FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19

Ni Tube (1/4 inch x 2m) , 500°C

$H_2 : O_2 = 67\% : 33\%$




FIG. 20

Ni Filter

$H_2 : O_2 = 67\% : 33\%$, 25scc/min






FIG. 21






FIG. 22




FIG. 23

Ni Ribbon (t 0.3 x 20 x 1000mm) , 500°C

$H_2 : O_2 = 67\% : 33\%$




FIG. 24

500°C, 25scc/min

RESPONSIVENESS (AFTER STOP OF GAS SUPPLY)




FIG. 25




FIG. 26




FIG. 27






FIG. 28






FIG. 29




FIG. 30






FIG. 31

H₂: 100scc/min
O₂: 33scc/min
620°C

H₂: O₂ = 3 : 1




FIG. 32

$H_2 : O_2 = 4 : 3$




FIG. 33




FIG. 34




FIG. 35




FIG. 36




FIG. 37




FIG. 40

NO.3 TEST




FIG. 41




FIG. 42




FIG. 43




FIG. 44




FIG. 45




FIG. 46




FIG. 47




FIG. 48






FIG. 50






FIG. 51




FIG. 52




FIG. 53

